



SAVONA

Porcelain Tile





30 x 60 cm (12" x 24")

SAVONA - Bianco



60 x 120 cm (24"x48")
SAVONA - Bianco Rectified



30 x 60 cm (12" x 24")
SAVONA - Bianco



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Bianco
Mosaics



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Bianco
Basketweave Mosaics



(33 x 33 cm Sheet)
(13" x 13" Sheet)
SAVONA - Bianco
Random Stripe



30 x 60 cm (12" x 24")

SAVONA - Smoke



60 x 120 cm (24"x48")
SAVONA - Smoke Rectified



30 x 60 cm (12" x 24")
SAVONA - Smoke



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Smoke
Mosaics



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Smoke
Basketweave Mosaics



(33 x 33 cm Sheet)
(13" x 13" Sheet)
SAVONA - Smoke
Random Stripe



30 x 60 cm (12" x 24")

SAVONA - Ash



60 x 120 cm (24"x48")
SAVONA - Ash Rectified



30 x 60 cm (12" x 24")
SAVONA - Ash



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Ash
Mosaics



5 x 5 cm (30 x 30 cm Sheet)
2" x 2" (12" x 12" Sheet)
SAVONA - Ash
Basketweave Mosaics



(33 x 33 cm Sheet)
(13" x 13" Sheet)
SAVONA - Ash
Random Stripe


PACKING INFORMATION

PRODUCT	THICKNESS	Pcs x Box	Sqm x Box	Sqft x Box	Kgs x Box	Lbs x Box	Box x Pal	Sqm x Pal	Sqft x Pal	Kgs x Pal	Lbs x Pal
30 x 60 cm - (12"x24") SAVON	9,0 mm. - 0,36"	9	1,62	17,43	28,4	62,60	32	51,84	558,00	933	2056
60 x 120 cm - (24"x48") SAVONA Rectified	11 mm. - 0,44"	2	1,44	15,49	33,7	74,30	25	36,00	387,36	867,5	1912
5 x 5 cm (2"x2") - 30 x 30 cm (12"x12") SAVONA Mosaics	9,0 mm. - 0,36"	10	0,88	9,47	18	39,68	48	42,34	455,74	894	1971
33 x 33 cm - (13"x13") SAVONA Random Stripe	9,0 mm. - 0,36"	10	1,06	11,41	17	37,48	48	50,85	547,34	846	1865
5 x 5 cm (2"x2") - 30 x 30 cm (12"x12") SAVONA Basketweave Mosaics	9,0 mm. - 0,36"	10	0,90	9,69	18	39,68	48	43,20	465,00	894	1971

GENERAL SPECIFICATIONS

TECHNICAL FEATURES	NORMS	PORCELAIN TILE		MONTECERA AVERAGE VALUE
		Requirement for Nominal Size N.		
		7 cm ≤ N < 15 cm	N ≥ 15 cm	MATT
LENGTH AND WIDTH	EN ISO 10545-2	± 0,90 mm	± 0,6% ±2,0 mm	Confirmed
THICKNESS	EN ISO 10545-2	± 0,50 mm	± 0,5%	Confirmed
STRAIGHTNESS	EN ISO 10545-2	± 0,75 mm	± 0,5% ±1,5 mm	Confirmed
SQUARNESS	EN ISO 10545-2	± 0,75 mm	± 0,6% ±2,0 mm	Confirmed
SURFACE FLATNESS	EN ISO 10545-2	± 0,75 mm	± 0,5% ±2,0 mm	Confirmed
WATER ABSORPTION	EN ISO 10545-3	≤ 0,5%		≤ 0,5%
BREAKING STRENGTH	EN ISO 10545-4	1300 N		1400 N
MODULUS OF RUPTURE	EN ISO 10545-4	≥ 35 N/mm ²		≥ 40 N/mm ²
THERMAL SHOCK RESISTANCE	EN ISO 10545-9	Required		Resistant
FROST RESISTANCE	EN ISO 10545-12	Required		Resistant
CHEMICAL RESISTANCE	EN ISO 10545-13	Indicated by manufacturer		Resistant
RESISTANCE TO STAINS	EN ISO 10545-14	Indicated by manufacturer		Resistant
DCOF (Wet)	ANSI B 101.3	Indicated by manufacturer		> 0,42
SCRATCH HARDNESS (MOHS)		Indicated by manufacturer		Min. 6
ABRASION RESISTANCE (PEI)	EN ISO 10545-7	Indicated by manufacturer		4
SHADE VARIATION		Indicated by manufacturer		V2